



Belt Conditioner, 7.5 Wt Oz
 No. 05350 | Item# 1003783 | Case# 1003780

Product Description	Eliminates squeaks and prolongs belt life. For use on all types of belts, such as serpentine, flat and v-type belts. Prevents slippage and glazing. Removes oil, grease and glaze. Use every 3,000 miles to prevent drying out and slippage.
Applications	Belts, canvas belts, fabrics, flat belts, leather belts, round belts, rubber, V-belts
Unit Package Description	10 Ounce Aerosol
Brand	CRC
Generic Description 1	Food Grade Synthetic Lubricant
Net Fill	7.5 Wt Oz
UPC Code	078254053509
Unit Dimensions	6.25H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	6.7H x 8.3W x 11.1D in
Cases Per Pallet	171
Case Weight	9 lbs
I 2 of 5 Code	30078254053500
Appearance	Colorless Liquid
Base Type	Polyisobutene
Flash point (F)	16°F
Flash point (C)	-9°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.7
Plastic Safe	Yes
Film Type	Tacky, Colorless, Non-Drying
Evaporation Rate	Fast
Dielectric Strength	26,600 Volts/Mil
Working Temp (F)	Max 350°F
Working Temp (C)	Max 176.7°C

Last revised: 8/19/2019
 Page 1 of 2





Propellant	Hydrocarbon
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	92.7
VOC g/L (Consumer Product def)	628
VOC lbs/gal (Consumer Prod def)	5.24
VOC Category	Not Regulated
Removal (How To)	Remove with mineral spirits or HF™ Contact Cleaner.