



Blu Tack

A RE-USABLE ADHESIVE

Date: 15 September 2015

Fact Sheet No.: TDS00548

YOUR SMART ADVANTAGES

- Clean, safe and easy to use
- An ideal alternative to drawing pins and sticky tape
- ISO 9002 Quality Assured Firm

USES

Bostik Blu Tack is a permanently plastic, reusable adhesive. Bostik Blu Tack is supplied in the form of rectangular slabs between sheets of release paper and packed in individual wallets. Bostik Blu Tack is clean and economical in use.

Holds up posters, cards, children's paintings, party decorations, maps, messages, etc. Telephones and calculators to desks, ornaments to shelves, photos in albums, screws to screwdrivers, model parts during painting, etc.

Holds safety pins, keys, screws, etc. flowers and candles in place for table and flower arrangements.

Cleans fluff from fabric and dirt from typewriters, model railway tracks, etc. May be rolled and manipulated to make 3 dimensional artistic 'models'.

For use on non-porous surfaces: - vinyl coated wallpapers, painted surfaces, glass, and metal.

PRODUCT CHARACTERISTICS

Colour	Pale blue
Form	Rectangular slab
Specific Gravity	1.8 approx.
Composition	Synthetic polymer base

Product Code	30813254 Blu Tack Handy x 12 Wallets
	308590110 Blu Tack Economy x 12 Wallets
	30813273 Blu Tack Handy Clip Strip
Storage/Shelf Life	Store for up to 60 months from date of manufacture when stored in the original, unopened packaging under dry conditions within the temperature range of +15°C to +30°C.

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Blu Tack refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

PREPARATION

1. Make certain that the surfaces to which Bostik Blu Tack is to be applied are clean, dry and free from dust, grease and loose surface material.

APPLICATION

2. Simply tear off the amount of Bostik Blu Tack required, pull and stretch until supple, then roll into a ball. Place this between the surfaces to be fastened and press firmly.

REMOVAL

3. To remove Bostik Blu Tack roll it carefully off the surface. It can then be used again and again. Any remaining shreds can be removed by rolling or dabbing a blob of Bostik Blu Tack over the surfaces.
4. The adhesive properties of Bostik Blu Tack increase with time so take extra care when removing it after a period of months. On some surfaces Bostik Blu Tack may leave an oily mark but lighter fuel (flammable) or proprietary chewing gum remover (non-flammable) can sometimes remove this.



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

- The effect of these liquids on the particular surface concerned should first be tested on a small, inconspicuous area.

PRECAUTIONS IN USE

Do not use Bostik Blu Tack on absorbent, silk-screen printed or hand stencilled wallpaper, or on porous brickwork.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Blu Tack, available at www.bostik.co.uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



FM 01696
BS EN ISO 9001:2008

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01785 272625	Fax: 01785 212962	stafford.gatehouse@bostik.com



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk
Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.