



Honing & Cutting Oil, 1 Gal

No. SL2523 | Item# 1007833 | Case# 1007832

Product Description	An all-purpose metal working/ cutting lubricant that extends tool life and improves machined surface finish.
Applications	Valve refacing, piston pin fitting, honing, tapping, reaming, grinding, threading, boring, broaching, drilling and milling
Unit Package Description	1 Gallon Bottle
Brand	Sta-Lube
Generic Description 1	Honing & Cutting Oil
Net Fill	1 Gal
UPC Code	072213252309
Unit Dimensions	10.63H x 4.75W x 6D in
Units Per Case	4
Case Dimensions	11.25H x 11.25W x 13.5D in
Cases Per Pallet	60
Case Weight	33 lbs
I 2 of 5 Code	30072213252300
Appearance	Red Liquid
Flash point (F)	378°F
Flash point (C)	192°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.89
Plastic Safe	Not Determined
Evaporation Rate	Slow
ISO Viscosity Grade	32
Working Temp (F)	50 to 150°F
Working Temp (C)	10 to 65.6°C
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	2.9

Last revised: 11/15/2019

Page 1 of 2



Chemical Solutions to Keep You Moving™

f t i n • 800-272-8963 • crcindustries.com



VOC g/L (Consumer Product def)	26
VOC lbs/gal (Consumer Prod def)	0.2
VOC Category	Cutting or Tapping Oil (Non-Aerosol)
Restricted from Sale In:	SCAQMD
Removal (How To)	Remove with a general purpose degreaser