



## Super White<sup>™</sup> Multi-Purpose Lithium Grease, 14 Wt Oz No. SL3150 | Item# 1007873 | Case# 1007872

Product Description A high purity, NLGI Grade 1.5 multi-purpose white lithium

grease. Provides superior lubrication & durability in any weather and most temperatures. Bright white in color.

Ideal for when appearance is important.

Applications Assembly lubes, bearings, break-in lubrication for

bearings, cables, chains, chassis points, conveyor bearings, door tracks, garage door channels & openers, hinges, latches, machinery, open gears, overhead door

tracks, roller bearings, sleeve bearings.

Unit Package Description 14 Ounce Cartridge

Brand Sta-Lube

Generic Description 1 Super White Multi-Purpose Grease

Net Fill 14 Wt Oz

UPC Code 072213315004

Unit Dimensions 9.31H x 2.13W x 2.13D in

Units Per Case 10

Case Dimensions 9.5H x 4.5W x 11.38D in

Cases Per Pallet 150
Case Weight 11 lbs

I 2 of 5 Code 30072213315005

Appearance White Semi-Solid to Solid Grease

Base Type Lithium-12

Flash point (F) 475°F Flash point (C) 246°C Flammability Class - CPSC None

Spec Gravity Concentrate 0.9 at 60°F

NLGI Grade 1.5 Timken OK Load Lbs. 25 Lbs

Plastic Safe Not Determined

Evaporation Rate <0.01 (Butyl Acetate=1)

Last revised: 4/23/2019

Page 1 of 2







Working Temp (F) 0 to 300°F

Working Temp (C) -17.8 to 148.9°C

5

None

< 0.01

**Drop Point** 350°F

Leakage Oil Separation 5

Oxidation Stability 10

Pour Point (F) 0°F

Pour Point (C) -17.78°C

ISO Viscosity Grade 165 Water Washout 10%

Worked Penetration 285 to 295

**NSF Category Code** H2

**NSF Number** 147593

**DOT Proper Shipping Name** Not Regulated

VOC % (Consumer Product < 0.1

def)

VOC g/L (Consumer < 0.9

Product def)

VOC lbs/gal (Consumer

Propellant

Prod def)

**VOC Category** Not Regulated

Removal (How To) Remove with a degreaser or brake cleaner product.

Last revised: 4/23/2019

Page 2 of 2

