



**Constant Velocity (CV) Joint Grease, 4 Wt Oz**  
 No. SL3174 | Item# 1007886 | Case# 1007885

Product Description	A special lithium base grease fortified with molybdenum disulfide and polymers. It is used for the installation & repair work on CV joints. Will extend the life of the CV joint & the additives will sustain the shock loads encountered in the CV joints
Applications	CV boot, CV joints found in front wheel drive passenger vehicles, safe for both domestic & foreign CV joints
Unit Package Description	4 ounce Tube
Brand	Sta-Lube
Generic Description 1	Constant Velocity Joint Grease
Net Fill	4 Wt Oz
UPC Code	072213317404
Unit Dimensions	9.25H x 4W x 1.5D in
Units Per Case	12
Case Dimensions	9.75H x 5.13W x 11D in
Cases Per Pallet	175
Case Weight	5 lbs
I 2 of 5 Code	30072213317405
Appearance	Dark Gray Semi-Solid to Solid Grease
Base Type	Lithium-12
Flash point (F)	>450°F
Flash point (C)	>232°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.9 at 60°F
NLGI Grade	1
Timken OK Load Lbs.	50 Lbs
Plastic Safe	Yes
Evaporation Rate	<0.01 (Butyl Acetate=1)
Working Temp (F)	10 to 275°F
Working Temp (C)	-12.2 to 134°C

Last revised: 4/23/2019  
 Page 1 of 2





4 Ball EP	Not Determined
4 Ball Wear	Not Determined
Drop Point	350°F
Elastomer Compatibility	0 to 40% vol ; 0 to 15 hard
Leakage	Not Determined
Oil Separation	<10%
Oxidation Stability	<5 Lbs
Pour Point (F)	10°F
Pour Point (C)	-12.22°C
ISO Viscosity Grade	110
Water Washout	Not Determined
Worked Penetration	300 to 330
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	<0.1
VOC g/L (Consumer Product def)	<0.9
VOC lbs/gal (Consumer Prod def)	<0.007
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 4/23/2019  
Page 2 of 2

