



Marine Boat Trailer and 4x4 Wheel Bearing Grease, 3 Wt Oz
 No. SL3184 | Item# 1007888 | Case# 1007887

Product Description

A blue tacky, aluminum complex grease using a highly refined base oil. It has been formulated with a polymer to provide adhesive, non-blend and water wash-out characteristics. Will resist water under the most severe water conditions.

Applications

Anti-friction bearings, blocks, boat trailer bearings, deck equipment, marine equipment, shaft log seals, sleeve bearings, slides, steering cables, steering dockside machinery, steering quadrants, turnbuckles, wheel bearings, winches

Unit Package Description

3 Each 3 Ounce Cartridge

Brand

Sta-Lube

Generic Description 1

Marine Grease for Boat Trailer

Net Fill

3 Wt Oz

UPC Code

072213318401

Unit Dimensions

8.5H x 6.25W x 1.5D in

Units Per Case

6

Case Dimensions

9H x 9.13W x 6.56D in

Cases Per Pallet

140

Case Weight

5 lbs

I 2 of 5 Code

30072213318402

Appearance

Blue Semi-Solid to Solid Grease

Base Type

Aluminum Complex

Flash point (F)

>450°F

Flash point (C)

>232.2°C

Flammability Class - CPSC

None

Spec Gravity Concentrate

0.9

NLGI Grade

2

Plastic Safe

Not Determined

Evaporation Rate

Slow

Working Temp (F)

0 to 325°F

Last revised: 1/16/2019

Page 1 of 2





Working Temp (C)	-17.8 to 162°C
Drop Point	500°F
Leakage	5
Oxidation Stability	5
Pour Point (F)	0°F
Pour Point (C)	-17.78°C
ISO Viscosity Grade	180 Cst at 40°C
Water Washout	5% at 175°F
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 1/16/2019
Page 2 of 2