# SAFETY DATA SHEET

# 1. Identification

**Product identifier** Sta-Plex™ Premium Red Grease

Other means of identification

No. SL3192 (Item# 1007894) **Product Code** 

Recommended use Lubricating grease Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

CRC Industries. Inc. Company name 885 Louis Dr. **Address** 

Warminster, PA 18974 US

Telephone

215-674-4300 **General Information Technical Assistance** 800-521-3168 **Customer Service** 800-272-4620 24-Hour Emergency 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International) Website www.crcindustries.com

# 2. Hazard(s) identification

Category 1 **Physical hazards** Flammable aerosols

> Gases under pressure Liquefied gas Skin corrosion/irritation Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1 Category 2

**Environmental hazards** Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment,

long-term hazard

Not classified. **OSHA** defined hazards

Label elements

**Health hazards** 



Signal word Danger

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if **Hazard statement** swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Toxic to

aquatic life. Harmful to aquatic life with long lasting effects.

**Precautionary statement** 

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Wear protective gloves. Avoid release to the environment.

Category 3

Material name: Sta-Plex™ Premium Red Grease

SDS US No. SL3192 (Item# 1007894) Version #: 02 Revision date: 01-24-2018 Issue date: 05-21-2015

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash Response

with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for

breathing. Call a poison center/doctor if you feel unwell.

Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to **Storage** 

temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Dispose of contents/container in accordance with local/regional/national regulations. Disposal

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
heptane, branched, cyclic and linear		426260-76-6	40 - 50
mineral oil		Mixture	30 - 40
propane		74-98-6	10 - 20
aluminum hydroxide benzoate stearate		54326-11-3	5 - 10

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get Skin contact

medical advice/attention. Wash contaminated clothing before reuse.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and

delayed

Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up.

General fire hazards

Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when

exposed to heat or flame.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

U.S. - OSHA

Components	Туре	Value	
mineral oil	TWA	5 mg/m3	
US. OSHA Table Z-1 Limits for A	ir Contaminants (29 CFR 1910.10	000)	
Components	Туре	Value	
propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
ACGIH			
Components	Туре	Value	Form
mineral oil	TWA	5 mg/m3	Inhalable fraction
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	Form
aluminum hydroxide	TWA	1 mg/m3	Respirable fraction.
benzoate stearate (CAS 54326-11-3)			
U.S NIOSH			
Components	Туре	Value	Form
mineral oil	STEL	10 mg/m3	Mist
	TWA	5 mg/m3	Mist

Material name: Sta-Plex™ Premium Red Grease

**US. NIOSH: Pocket Guide to Chemical Hazards** 

 Components
 Type
 Value

 propane (CAS 74-98-6)
 TWA
 1800 mg/m3

1000 ppm

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear protective gloves such as: Nitrile. Neoprene.

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** 

**Physical state** Liquid. Aerosol. **Form** Color Red. Solvent. Odor **Odor threshold** Not available. pН Not available. Not available. Melting point/freezing point Initial boiling point and boiling 175 °F (79.4 °C)

range

Flash point  $< 20 \,^{\circ}\text{F} (< -6.7 \,^{\circ}\text{C})$ 

**Evaporation rate** Fast.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower 1.2

(%)

Flammability limit - upper 6.7

(%)

Vapor pressure 2544.3 hPa estimated

Vapor density > 1 (air = 1)

Relative density 0.67 estimated

Solubility(ies)

Solubility (water) Slightly soluble.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature

Not available.

Decomposition temperature

Not available.

Decomposition temperature

Not available.

Percent volatile

94.4 % estimated

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**Conditions to avoid** Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

#### 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

**Skin contact** Causes skin irritation.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Ingestion** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness.

Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

#### Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components	Species	Test Results
------------	---------	--------------

heptane, branched, cyclic and linear (CAS 426260-76-6)

<u>Acute</u>

**Dermal** 

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 60 mg/l, 4 hours

Oral

LD50 Rat > 5000 mg/kg

mineral oil

<u>Acute</u>

**Dermal** 

LD50 Rabbit > 2000 mg/kg

Inhalation

Vapor

LC50 Rat 2180 mg/kg, 4 hours

Oral

LD50 Rat > 5000 mg/kg

propane (CAS 74-98-6)

**Acute** 

**Dermal** 

LD50 Rabbit > 5000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Material name: Sta-Plex™ Premium Red Grease

SDS US

No. SL3192 (Item# 1007894) Version #: 02 Revision date: 01-24-2018 Issue date: 05-21-2015

Not classifiable as to carcinogenicity to humans. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

**US. National Toxicology Program (NTP) Report on Carcinogens** 

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

May cause drowsiness and dizziness.

single exposure

Specific target organ toxicity -

repeated exposure

Not classified.

May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, **Aspiration hazard** 

may cause chemical pneumonia, pulmonary injury or death.

**Chronic effects** Prolonged inhalation may be harmful.

12. Ecological information

Toxic to aquatic life. Harmful to aquatic life with long lasting effects. **Ecotoxicity** 

Components **Test Results** 

heptane, branched, cyclic and linear (CAS 426260-76-6)

Aquatic

Acute

Crustacea EC50 Water flea (Daphnia magna) 1.5 mg/l, 48 hours

mineral oil

Aquatic

Acute

EC50 Crustacea > 10000 mg/l, 48 hours Water flea (Daphnia magna) Fish LC50 Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

propane 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or **Disposal instructions** 

dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not

puncture, incinerate or crush. Dispose in accordance with all applicable regulations.

D001: Waste Flammable material with a flash point <140 F Hazardous waste code

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

**UN** number UN1950

**UN** proper shipping name

Transport hazard class(es)

Aerosols, flammable, Limited Quantity

2.1 Class Subsidiary risk 2.1 Label(s)

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions

Material name: Sta-Plex™ Premium Red Grease No. SL3192 (Item# 1007894) Version #: 02 Revision date: 01-24-2018 Issue date: 05-21-2015

306 Packaging exceptions Packaging non bulk 304 Packaging bulk None

**IATA** 

UN1950 **UN** number

**UN proper shipping name** Aerosols, flammable, Limited Quantity

Transport hazard class(es)

Class 2.1 Subsidiary risk

Not applicable. Packing group

**ERG Code** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

**IMDG** 

UN1950 **UN** number

**UN** proper shipping name AEROSOLS, Limited Quantity

Transport hazard class(es)

2 **Class** Subsidiary risk

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No. F-D. S-U **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

### 15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

**CERCLA Hazardous Substances: Reportable quantity** 

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

# Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

**Food and Drug** Not regulated.

Administration (FDA)

Material name: Sta-Plex™ Premium Red Grease

SDS US

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard

Flammable (gases, aerosols, liquids, or solids)

categories

Gas under pressure

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

#### SARA 302 Extremely hazardous substance

Not listed.

#### SARA 313 (TRI reporting)

Not regulated.

#### **US state regulations**

#### US. New Jersey Worker and Community Right-to-Know Act

propane (CAS 74-98-6)

#### **US. Massachusetts RTK - Substance List**

propane (CAS 74-98-6)

#### US. Pennsylvania Worker and Community Right-to-Know Law

propane (CAS 74-98-6)

#### **US. Rhode Island RTK**

propane (CAS 74-98-6)

#### **California Proposition 65**



WARNING: Cancer - www.P65Warnings.ca.gov

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

C.I. Solvent Yellow 14 (CAS 842-07-9)

C.I. Solvent Yellow 3 (CAS 97-56-3)

Eisted: May 15, 1998

Listed: July 1, 1987

Eisted: June 11, 2004

#### Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

51.100(s))

63 %

Consumer products (40 CFR 59, Subpt. C)

Not regulated

State

**Consumer products** 

Not regulated

VOC content (CA) 63 % VOC content (OTC) 63 %

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Toxic Chemical Substances (TCS)	No

Material name: Sta-Plex™ Premium Red Grease

Country(s) or region Inventory name On inventory (yes/no)\*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

# 16. Other information, including date of preparation or last revision

05-21-2015 Issue date 01-24-2018 **Revision date** Allison Yoon Prepared by

02 Version #

**HMIS®** ratings Health: 2

Flammability: 4 Physical hazard: 0 Personal protection: B

NFPA ratings Health: 2

Flammability: 4 Instability: 0

NFPA ratings



The information contained in this document applies to this specific material as supplied. It may not Disclaimer

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

This document has undergone significant changes and should be reviewed in its entirety. **Revision information** 

No. SL3192 (Item# 1007894) Version #: 02 Revision date: 01-24-2018 Issue date: 05-21-2015