



## Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 17

TEROSON SB 3120 AE

SDS No. : 507233  
V003.0

Revision: 13.04.2018

printing date: 20.01.2020

Replaces version from: 06.10.2016

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

TEROSON SB 3120 AE

#### Contains:

Naphtha (petroleum), hydrotreated heavy (<0.1% benzene)  
Hydrocarbons, C9-unsatd., polymd.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:  
Underbody coating

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd  
Wood Lane End  
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000  
Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Flammable aerosols Category 1  
H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.

**Skin sensitizer** Category 1

**H317 May cause an allergic skin reaction.**

Specific target organ toxicity - single exposure Category 3

H336 May cause drowsiness or dizziness.


Target organ: Central Nervous System

**Chronic hazards to the aquatic environment** Category 2

**H411 Toxic to aquatic life with long lasting effects.**

#### 2.2. Label elements

##### Label elements (CLP):

<b>Hazard pictogram:</b>	
<b>Signal word:</b>	Danger
<b>Hazard statement:</b>	<p>H222 Extremely flammable aerosol.  H229 Pressurised container: May burst if heated.  H317 May cause an allergic skin reaction.  H336 May cause drowsiness or dizziness.  H411 Toxic to aquatic life with long lasting effects.</p>
<b>Supplemental information</b>	EUH066 Repeated exposure may cause skin dryness or cracking.
<b>Precautionary statement:</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  No smoking.  P211 Do not spray on an open flame or other ignition source.  P251 Do not pierce or burn, even after use.  P261 Avoid breathing vapours.  P273 Avoid release to the environment.  P280 Wear protective gloves/protective clothing/eye protection/face protection.</p>

### 2.3. Other hazards

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.

The solvent vapors are heavier than air and may collect in high concentrations at floor level.

The aerosol container is under pressure. Do not expose to high temperatures.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General chemical description:

Underbody coating, containing solvents

#### Base substances of preparation:

Styrene-butadiene copolymer

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	265-150-3 01-2119463258-33	20- 40 %	Flam. Liq. 3 H226 Asp. Tox. 1 H304 STOT SE 3 H336
Dimethyl ether 115-10-6	204-065-8 01-2119472128-37	20- 40 %	Flam. Gas 1 H220 Press. Gas H280
Nonane 111-84-2	203-913-4	1- < 3 %	Flam. Liq. 3 H226 Asp. Tox. 1 H304 Skin Irrit. 2 H315 STOT SE 3 H336 Aquatic Acute 1 H400 Aquatic Chronic 1 H410
zinc oxide 1314-13-2	215-222-5 01-2119463881-32	0,25- < 2,5 %	Aquatic Chronic 1 H410 Aquatic Acute 1 H400
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	01-2119555292-40	0,1- < 1 %	Aquatic Chronic 3 H412 Skin Sens. 1A H317

For full text of the H - statements and other abbreviations see section 16 "Other information".  
Substances without classification may have community workplace exposure limits available.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

IF ON SKIN: Wash with plenty of soap and water.

In case of adverse health effects seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

not relevant.

### 4.2. Most important symptoms and effects, both acute and delayed

Repeated exposure may cause skin dryness or cracking.

Vapors may cause drowsiness and dizziness.

SKIN: Rash, Urticaria.

### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media:

All common extinguishing agents are suitable.

#### Extinguishing media which must not be used for safety reasons:

Water jet (solvent-containing product).

### 5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

### 5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

Keep unprotected persons away.

Danger of slipping on spilled product.

### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

Inform authorities in the event of product spillage to water courses or sewage systems.

### 6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

### 6.4. Reference to other sections

See advice in section 8

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid open flames and sources of ignition.

Use explosion proof electric equipment.

Use only non-sparking tools.

Ground/bond container and receiving equipment.

Take precautionary measures against static discharge.

#### Hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

### 7.2. Conditions for safe storage, including any incompatibilities

The storage regulations for aerosols apply.

Ensure good ventilation/extraction.

Store in a cool place.

Protect from direct sunlight.

Storage at 15 to 20°C is recommended.

### 7.3. Specific end use(s)

Underbody coating

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational Exposure Limits

Valid for  
Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Dimethyl ether 115-10-6 [DIMETHYL ETHER]	500	958	Short Term Exposure Limit (STEL):		EH40 WEL
Dimethyl ether 115-10-6 [DIMETHYL ETHER]	400	766	Time Weighted Average (TWA):		EH40 WEL
Dimethyl ether 115-10-6 [DIMETHYLETHER]	1.000	1.920	Time Weighted Average (TWA):	Indicative	ECLTV
Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Carbon black 1333-86-4 [CARBON BLACK]		3,5	Time Weighted Average (TWA):		EH40 WEL
Carbon black 1333-86-4 [CARBON BLACK]		7	Short Term Exposure Limit (STEL):		EH40 WEL

#### Occupational Exposure Limits

Valid for  
Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Dimethyl ether 115-10-6 [DIMETHYL ETHER]	1.000	1.920	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Dimethyl ether 115-10-6 [DIMETHYLETHER]	1.000	1.920	Time Weighted Average (TWA):	Indicative	ECLTV
Limestone		4	Time Weighted Average		IR_OEL

1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]			(TWA):		
Limestone 1317-65-3 [CALCIUM CARBONATE, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL
Nonane 111-84-2 [NONANE, ALL ISOMERS]	200	1.050	Time Weighted Average (TWA):		IR_OEL
Zinc oxide 1314-13-2 [ZINC OXIDE, FUME (RESPIRABLE FRACTION)]		2	Time Weighted Average (TWA):		IR_OEL
Zinc oxide 1314-13-2 [ZINC OXIDE, FUME (RESPIRABLE FRACTION)]		10	Short Term Exposure Limit (STEL):		IR_OEL
Carbon black 1333-86-4 [CARBON BLACK (INHALABLE FRACTION)]		3	Time Weighted Average (TWA):		IR_OEL

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Dimethyl ether 115-10-6	aqua (freshwater)		0,155 mg/l				
Dimethyl ether 115-10-6	sediment (freshwater)				0,681 mg/kg		
Dimethyl ether 115-10-6	soil				0,045 mg/kg		
Dimethyl ether 115-10-6	sewage treatment plant (STP)		160 mg/l				
Dimethyl ether 115-10-6	aqua (marine water)		0,016 mg/l				
Dimethyl ether 115-10-6	aqua (intermittent releases)		1,549 mg/l				
Dimethyl ether 115-10-6	sediment (marine water)				0,069 mg/kg		
zinc oxide 1314-13-2	aqua (freshwater)		0,0206 mg/l				
zinc oxide 1314-13-2	aqua (marine water)		0,0061 mg/l				
zinc oxide 1314-13-2	sewage treatment plant (STP)		0,1 mg/l				
zinc oxide 1314-13-2	sediment (freshwater)				117,8 mg/kg		
zinc oxide 1314-13-2	sediment (marine water)				56,5 mg/kg		
zinc oxide 1314-13-2	soil				35,6 mg/kg		
zinc oxide 1314-13-2	Air						
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	Sewage treatment plant		2,2 mg/l				
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	aqua (freshwater)		54 µg/l				
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	aqua (intermittent releases)		540 µg/l				
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	aqua (marine water)		5,4 µg/l				
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	sediment (freshwater)				1584 mg/kg		
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	sediment (marine water)				154 mg/kg		
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	soil				316,7 mg/kg		

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	Workers	dermal	Long term exposure - systemic effects		208 mg/kg	
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	Workers	Inhalation	Long term exposure - systemic effects		871 mg/m <sup>3</sup>	
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	General population	dermal	Long term exposure - systemic effects		125 mg/kg	
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	General population	Inhalation	Long term exposure - systemic effects		185 mg/m <sup>3</sup>	
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	General population	oral	Long term exposure - systemic effects		125 mg/kg	
Dimethyl ether 115-10-6	Workers	inhalation	Long term exposure - systemic effects		1894 mg/m <sup>3</sup>	
Dimethyl ether 115-10-6	General population	inhalation	Long term exposure - systemic effects		471 mg/m <sup>3</sup>	
zinc oxide 1314-13-2	Workers	Inhalation	Long term exposure - systemic effects		5 mg/m <sup>3</sup>	
zinc oxide 1314-13-2	Workers	dermal	Long term exposure - systemic effects		83 mg/kg	
zinc oxide 1314-13-2	Workers	inhalation	Long term exposure - local effects		0,5 mg/m <sup>3</sup>	
zinc oxide 1314-13-2	General population	Inhalation	Long term exposure - systemic effects		2,5 mg/m <sup>3</sup>	
zinc oxide 1314-13-2	General population	dermal	Long term exposure - systemic effects		83 mg/kg	
zinc oxide 1314-13-2	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	Workers	inhalation	Long term exposure - systemic effects		3,3 mg/m <sup>3</sup>	
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	Workers	dermal	Long term exposure - systemic effects		4,7 mg/kg	
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	General population	inhalation	Long term exposure - systemic effects		0,58 mg/m <sup>3</sup>	
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	General population	dermal	Long term exposure - systemic effects		1,67 mg/kg	
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	General population	oral	Long term exposure - systemic effects		0,33 mg/kg	

**Biological Exposure Indices:**

None

**8.2. Exposure controls:**

## Engineering controls:

In case of aerosol forming ensure sufficient suction and ventilation.

## Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.



**Hand protection:**

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR;  $\geq 0.7$  mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Isobutylene-isoprene rubber (IIR;  $\geq 0.7$  mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**

Goggles which can be tightly sealed.  
Protective eye equipment should conform to EN166.

**Skin protection:**

Protective clothing that covers arms and legs.  
Wear protective equipment.  
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

**Advices to personal protection equipment:**

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway).

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance	aerosol liquid black
Odor	of solvent
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	136 - 138 °C (276.8 - 280.4 °F)
Flash point	22,5 °C (72.5 °F); no method
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	42,3 mbar
(55 °C (131 °F))	
Vapour pressure	52,4 mbar
(50 °C (122 °F))	
Relative vapour density:	No data available / Not applicable
Density	1,138 g/cm <sup>3</sup>
(20 °C (68 °F))	
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative)	Not miscible
(20,0 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	5.400 mPa.s
(Brookfield; 40 °C (104 °F))	
Viscosity (kinematic)	4.800 mm <sup>2</sup> /s
(40 °C (104 °F); )	
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

**9.2. Other information**

Flow cup viscosity (23 °C (73.4 °F) ; DIN EN ISO 2431; Viscosity by cup)	361 s
Ignition temperature	> 250 °C (> 482 °F)
max. VOC content:	681,7 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reaction with strong oxidants.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

Heat, flames, sparks and other sources of ignition.  
Temperatures over appr. 50 °C

### 10.5. Incompatible materials

See section reactivity.

### 10.6. Hazardous decomposition products

No decomposition if used according to specifications.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
zinc oxide 1314-13-2	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Hydrocarbons, C9- unsatd., polyimd. 71302-83-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)

#### Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
zinc oxide 1314-13-2	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Hydrocarbons, C9- unsatd., polyimd. 71302-83-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	LC50		vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Dimethyl ether 115-10-6	LC50	164000 ppm		4 h	rat	not specified
zinc oxide 1314-13-2	LC50	> 5,7 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
zinc oxide 1314-13-2	not irritating		rabbit	not specified

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
zinc oxide 1314-13-2	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
zinc oxide 1314-13-2	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Hydrocarbons, C9- unsatd., polymd. 71302-83-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Hydrocarbons, C9- unsatd., polymd. 71302-83-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Dimethyl ether 115-10-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
zinc oxide 1314-13-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
zinc oxide 1314-13-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
zinc oxide 1314-13-2	ambiguous	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

**Carcinogenicity**

No data available.

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	NOAEL P $\geq$ 20000 mg/m <sup>3</sup> NOAEL F1 $\geq$ 20000 mg/m <sup>3</sup>	Two generation study	inhalation: vapour	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

**STOT-single exposure:**

No data available.

**STOT-repeated exposure::**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9		inhalation: vapour	6 h/d, 5 d/w for 4 weeks daily	rat	OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	NOAEL 3.750 mg/kg	dermal	once per day	rat	OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Dimethyl ether 115-10-6	NOAEL > 10000 ppm	inhalation	4 week 6 hours/day, 5 days/week	rat	not specified
zinc oxide 1314-13-2	NOAEL 31,52 mg/kg	oral: feed	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

**Aspiration hazard:**

No data available.

**SECTION 12: Ecological information****General ecological information:**

Do not empty into drains, soil or bodies of water.

**12.1. Toxicity****Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Dimethyl ether 115-10-6	LC50	> 4.000 mg/l	96 h	Poecilia reticulata	OECD Guideline 203 (Fish, Acute Toxicity Test)
zinc oxide 1314-13-2	LC50	0,142 mg/l	96 h	Thymallus arcticus	OECD Guideline 203 (Fish, Acute Toxicity Test)
zinc oxide 1314-13-2	NOEC	0,44 mg/l	72 d	Oncorhynchus mykiss	other guideline:
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	LL50	25,8 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)

**Toxicity (Daphnia):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Dimethyl ether 115-10-6	EC50	> 4.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Nonane 111-84-2	EC50	0,2 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
zinc oxide 1314-13-2	EC50	1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	EL50	54 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

**Chronic toxicity to aquatic invertebrates**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
zinc oxide 1314-13-2	NOEC	0,058 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

**Toxicity (Algae):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Dimethyl ether 115-10-6	EC50	> 1.000 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
zinc oxide 1314-13-2	NOEC	0,017 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
zinc oxide 1314-13-2	EC50	0,17 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	EL50	> 100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	NOELR	100 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)

### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Dimethyl ether 115-10-6	EC10	> 1.600 mg/l	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)
zinc oxide 1314-13-2	IC50	5,2 mg/l	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	EC50	> 100 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

### 12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Dimethyl ether 115-10-6	not readily biodegradable.	aerobic	5 %	28 d	EU Method C.4-A (Determination of the "Ready" BiodegradabilityDissolved Organic Carbon (DOC) Die-Away Test)
Nonane 111-84-2	readily biodegradable	aerobic	100 %	25 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Dimethyl ether 115-10-6	0,07	25 °C	QSAR (Quantitative Structure Activity Relationship)
Nonane 111-84-2	5,65		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

### 12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) 64742-48-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Dimethyl ether 115-10-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
zinc oxide 1314-13-2	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
Hydrocarbons, C9-unsatd., polymd. 71302-83-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

### 12.6. Other adverse effects

No data available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080409

<b>SECTION 14: Transport information</b>
--

**14.1. UN number**

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

**14.2. UN proper shipping name**

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS (Nonane,Zinc oxide)
IATA	Aerosols, flammable

**14.3. Transport hazard class(es)**

ADR	2.1
RID	2.1
ADN	2.1
IMDG	2.1
IATA	2.1

**14.4. Packing group**

ADR  
RID  
ADN  
IMDG  
IATA

**14.5. Environmental hazards**

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

**14.6. Special precautions for user**

ADR	not applicable Tunnelcode: (D)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

<b>SECTION 15: Regulatory information</b>
---

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content (VOCV 814.018 VOC regulation CH)	58,2 %
VOC content (2010/75/EU)	59,8 %



**VOC Paints and Varnishes (EU):**

max. VOC content: 681,7 g/l

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H220 Extremely flammable gas.
- H226 Flammable liquid and vapor.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

**Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**