

VT-103EP / VT-105 / VT-121 / VT-126 SHOE ADHESIVE (TOLUENE-FREE)

Page: 1

Compilation date: 13/04/2018

Revision date: 26/02/2019

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: VT-103EP / VT-105 / VT-121 / VT-126 SHOE ADHESIVE (TOLUENE-FREE)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

- Company name: Vital Technical Sdn. Bhd.
 - No. 93, Jalan Industri 3/3,
 - Rawang Integrated Industrial Park,
 - Rawang
 - Selangor
 - 48000
 - Malaysia

Tel: +603 6094 2088

- Fax: +603 6099 2930
- Email: sales@vitaltechnical.com

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. Highly flammable liquid and

vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

| Label elements: | | | |
|--------------------|---|--|--|
| Hazard statements: | EUH066: Repeated exposure may cause skin dryness or cracking. | | |
| | H225: Highly flammable liquid and vapour. | | |
| | H319: Causes serious eye irritation. | | |
| | H336: May cause drowsiness or dizziness. | | |
| Hazard pictograms: | GHS02: Flame | | |
| | GHS07: Exclamation mark | | |
| | | | |



VT-103EP / VT-105 / VT-121 / VT-126 SHOE ADHESIVE (TOLUENE-FREE)

| Signal words: | Danger |
|---------------------------|---|
| Precautionary statements: | P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition |
| | sources. No smoking. |
| | P241: Use explosion-proof electrical/ventilating/lighting/ equipment. |
| | P280: Wear protective gloves/protective clothing/eye protection/face protection. |
| | P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. |
| | Rinse skin with water . |
| | P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for |
| | breathing. |
| | P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove |
| | contact lenses, if present and easy to do. Continue rinsing. |

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHYL METHYL KETONE

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|---------|-----------|---|---------|
| 201-159-0 | 78-93-3 | - | Flam. Liq. 2: H225; Eye Irrit. 2: H319; | 70-90% |
| | | | STOT SE 3: H336; -: EUH066 | |

ACETONE - REACH registered number(s): 01-2119471330-49

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

Ingestion: Wash out mouth with water.

Inhalation: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Page: 2

VT-103EP / VT-105 / VT-121 / VT-126 SHOE ADHESIVE (TOLUENE-FREE)

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised

personnel. Do not attempt to take action without suitable protective clothing - see section

8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

VT-103EP / VT-105 / VT-121 / VT-126 SHOE ADHESIVE (TOLUENE-FREE)

Page: 4

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ETHYL METHYL KETONE

| Workplace exposure limits: | | | | |
|---|--|-------------------------|---|--------------|
| State | 8 hour TWA | 15 min. STEL 8 hour TWA | | 15 min. STEL |
| UK | 600 mg/m3 | 899 mg/m3 | - | - |
| ACETONE | | | | |
| UK | 1210 mg/m3 | 3620 mg/m3 | - | - |
| DNEL/PNEC Values DNEL / PNEC No data available. | | | | |
| 8.2. Exposure controls | | | | |
| Engineering measures: Ensure there is sufficient ventilation of the area. | | | | |
| Respirat | Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. | | | gency. |
| н | Hand protection: Protective gloves. | | | |
| | Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand. | | | |

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| State: | Liquid | |
|-------------------------------|-------------------------------------|--------------------|
| | Colourless | |
| | | |
| Odour: | Sweet-smelling | |
| Evaporation rate: | No data available. | |
| Oxidising: | No data available. | |
| Solubility in water: | No data available. | |
| Viscosity: | Non-viscous | |
| Boiling point/range°C: | >35 Melting point/range°C: | No data available. |
| Flammability limits %: lower: | No data available. upper: | No data available. |
| Flash point°C: | <23 Part.coeff. n-octanol/water: | No data available. |
| Autoflammability°C: | No data available. Vapour pressure: | No data available. |
| Relative density: | 0.86 pH : | No data available. |
| VOC g/l: | No data available. | |
| | | |

VT-103EP / VT-105 / VT-121 / VT-126 SHOE ADHESIVE (TOLUENE-FREE)

Page: 5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ACETONE

| IVN | RAT | LD50 | 5500 | mg/kg |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 3000 | mg/kg |
| ORL | RAT | LD50 | 5800 | mg/kg |

Relevant hazards for product:

| Hazard | Route | Basis |
|-------------------------------|-------|-----------------------|
| Serious eye damage/irritation | OPT | Hazardous: calculated |
| STOT-single exposure | - | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

- **Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.
 - **Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

VT-103EP / VT-105 / VT-121 / VT-126 SHOE ADHESIVE (TOLUENE-FREE)

Page: 6 **Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Delayed / immediate effects: Immediate effects can be expected after short-term exposure. Section 12: Ecological information 12.1. Toxicity Hazardous ingredients: ACETONE **BLUEGILL** (Lepomis macrochirus) LC50 8300 mg/l 12.2. Persistence and degradability Persistence and degradability: Biodegradable. 12.3. Bioaccumulative potential Bioaccumulative potential: No bioaccumulation potential. 12.4. Mobility in soil Mobility: Readily absorbed into soil. 12.5. Results of PBT and vPvB assessment PBT identification: This product is not identified as a PBT/vPvB substance. 12.6. Other adverse effects Other adverse effects: Negligible ecotoxicity. Section 13: Disposal considerations 13.1. Waste treatment methods Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company. NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal. Section 14: Transport information 14.1. UN number UN number: UN1133 14.2. UN proper shipping name Shipping name: ADHESIVES 14.3. Transport hazard class(es)

Transport class: 3

VT-103EP / VT-105 / VT-121 / VT-126 SHOE ADHESIVE (TOLUENE-FREE)

Page: 7

Marine pollutant: No

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

| Other information: | according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation |
|------------------------------|--|
| | (EU) 2015/830 |
| | * indicates text in the SDS which has changed since the last revision. |
| Phrases used in s.2 and s.3: | EUH066: Repeated exposure may cause skin dryness or cracking. |
| | H225: Highly flammable liquid and vapour. |
| | H319: Causes serious eye irritation. |
| | H336: May cause drowsiness or dizziness. |
| Legal disclaimer: | The above information is believed to be correct but does not purport to be all inclusive |
| | and shall be used only as a guide. This company shall not be held liable for any |
| | damage resulting from handling or from contact with the above product. |